

## Installation

### 12FT/14FT/16FT VIKAN TRAMPOLINE ASSEMBLY INSTRUCTIONS

Before beginning to assemble your new VIKAN TRAMPOLINE, please check to make sure you have all the necessary parts.

- 1 box springs (12ft. 88 springs) (14ft. 100 springs) (16ft. 120 springs)
- 1 box trampoline jump mat
- 1 package pad
- 1 bundle 4 steel legs (16ft. 5 steel legs)
- 1 bundle 4 steel frames (16ft. 5 steel frames)

= 1 very happy family

Helpful Tip: Wear gloves to prevent cuts and pinches



#### Step 1:

Place 2 frame rail sections upside down. Insert 2 legs into stumps on each frame rail and turn right side up by holding legs and walking through and over the frame.



1-800-276-1621 or (604) 980-4645



**Step 2:**

Place remaining 2 frame rails sections onto leg uprights.



**Step 3:**

Now it is time to connect the male/female joints of the top frame rail sections. This can be done easily by pulling the rail outward and apart so that the joints can slide together.



**Step 4:**

Attach every 10<sup>th</sup> spring from the ▲ on jump mat to the frame. (12ft. every 8<sup>th</sup> spring)



#### Step 5:

A spring makes a great spring pulling tool and can prevent damage.



#### Step 6:

Attach the rest of the springs systematically every 5<sup>th</sup>, every 2<sup>nd</sup>, etc...





### Step 7:

Leave every 10<sup>th</sup> spring hanging. They need to be placed through the seat-belt webbing loop on the pad.



### Step 8:

Once you have tied down the safety pad straps the trampoline is ready for use. Have a great time on your new Vikan Trampoline.

**#1 Rule for Trampoline Safety  
One jumper at a time!**

## 8FT VIKAN TRAMPOLINE ASSEMBLY INSTRUCTIONS

Before beginning to assembly your new VIKAN TRAMPOLINE, please check to make sure you have all the necessary parts.

- 1 box containing 48 springs and trampoline mat
  - 1 box containing pads, set of 3 legs, set of 6 frame rail sections
- = 1 big happy family

Helpful Tip: Wear gloves to prevent cuts and pinches



### Step 1:

Place curved frame rail sections upside down and connect male/female joints.



### Step 2:

Insert legs into frame rails sockets while still upside down. Position each leg over the male/female frame connection.

Freedom Sports Ltd.  
1-800-276-1621  
(604) 980-4645



### Step 3:

Turn assembled frame and leg sections over and connect together completing circle.



### Step 4:

Connect every 8<sup>th</sup> spring to frame rail from every 8<sup>th</sup> ▲-ring on the trampoline mat.

Then every 4<sup>th</sup> and every 2<sup>nd</sup> until all 48 springs are connected.



### Step 5:

Place the pad on the springs and tie the black straps to the frame rails.

Now, **enjoy** but remember **the best rule for safety is one jumper at a time!**

Recommended weight load is 125 pounds to avoid bottoming out.